



GRAFIKLEEN[®] R845

Ink & Coating Remover

FEATURES/BENEFITS

Features

- Contains no CFCs
- High flash point (145°F TCC)
- Multiple uses
- Fast cleaning

Benefits

- Safer for employees to use
- Cost effective

Grafikleen R845 is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

VOC (method 24) 100%, 7.50 lbs/gl, 900 gms/l

Grafikleen R845 is a state of the art ink and coating remover with a higher flash point than traditional ink and coating removers. *Grafikleen R845* is also excellent for removing adhesives. The solvent present in *Grafikleen R845* is as effective as xylene, mineral spirits, naphtha and alcohols in the cleaning of solvent soluble inks and coatings. The high flash point of *Grafikleen R845* represents a significant reduction in the fire and explosion hazards that typically accompany this type of product.

Directions for Use

For the removal of hardened inks and adhesives, apply *Grafikleen R845* by coarse spray or rag and allow to dwell for a short time. Some brushing or agitation may be necessary in areas with a heavy buildup. Remove *Grafikleen R845* by wiping area with either a dry rag or mop. In some instances, a rag or mop slightly saturated with *Grafikleen R845* may be beneficial.

Grafikleen R845 can also be used in immersion cleaning. Temperatures should not exceed 110° F (43° C).

IMPORTANT: Before using **GRAFIKLEEN R845**, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (May06)